



Brand: BendPak
Model: MLS-16
Description: Mobile High-Lift Jack Stand

The MLS-16 is a support stand to be used to support raised heavy duty vehicles, to facilitate maintenance and inspection procedures. The support stand is designed to be used in sets of 4, 6 or 8 and must be placed under a level, raised vehicle, at the support points designated by the vehicle manufacturer.

- Each MLS-16 has a maximum rated capacity of 16,000 pounds.
- Tripod design; each of the three (3) legs will evenly distribute the supported weight.
- Each leg is equipped with a 6" square inch floor pad.
- Can be easily moved and placed under a vehicle by means of two 5" diameter wheels.
- Equipped with a fold-away transport handle.
- Center tube is spring assisted to facilitate adjustment of the stand.
- Adjustable from 54" to 78"
- 10 pin positions
- 2.25" diameter self-locking ACME screw for fine adjustment of the stand height.



Specifications

- | | |
|---------------------------|----------------------------|
| • Minimum height | 54" |
| • Maximum height | 78" |
| • Number of pin positions | 10 |
| • Screw fine adjustment | 6" / Adjustment Capability |
| • Stroke | 26 inches |
| • Base diameter | 32" |
| • Wheels / Diameter | 5" |
| • Top Pad Diameter | 7-1/4" |
| • Stand capacity | 16, 000 Lbs. |