

PL-7000XR



Parking Lifts

SKU# 5175454

7,000-lb. Capacity / Two-Post Parking Lift

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

The Only Parking Lift You May Ever Need

If you want to make the most out of your limited parking space, whether it's personal or commercial, then you need a premium [parking lift](#). BendPak's PL-7000XR two-post parking lift elegantly gets twice as much out of a single parking space. Its minimal footprint allows for multiple installations within limited spaces. Plus, with the extended height, this lift can easily accommodate taller vehicles, taking your parking capabilities to new heights. With a 7,000-lb. capacity, dual-hydraulic cylinder, wide-deck platform and integrated key-activated power switch, the PL-7000XR parking lift represents unparalleled convenience and versatility for just about any parking situation.

Features

- 7,000-lb. lifting capacity auto stacker parking lift
- Small footprint allows multiple installs in limited space
- Independent structures allows for staggered installation
- Power-unit and controls integrated within lift structure
- Freestanding design reduces tax and permit liabilities
- Overhead power unit provides quiet hydraulic operation
- Wide platform accommodates pickups, vans and cars
- Designed for installation on typical parking surfaces
- Durable construction for maximum stability
- Dual hydraulic cylinders and heavy-duty lifting chain
- Dual synchronization chains keeps the deck level under all conditions
- Automatic safety lock
- Maintenance-free composite carriage bearings
- Maintenance-free self-lubricating chain rollers
- Wide-base plate mounts directly on grade, even on asphalt
- No special site preparation required for installation
- Optional audible / visual descent alarm available
- Standard integrated key-activated power on / off switch



Specifications

Lifting Capacity 7,000 lbs. (3,175 kg)

Overall Width 98" (2,489 mm)

Overall Length 173.5" (4,405 mm)

Overall Height 131" (3,327 mm)

Platform Width 85" (2,165 mm)

Platform Length 157.5" (4,001 mm)

Lifting Time 30 sec

Standard Motor 220 VAC / 60 Hz / 1Ph

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.